

»CIERRAPUERTAS HIDAULICO GRADO 1 SERIE.4040

4040XP Extra Heavy Duty Closer

Mfg #	Arm Type	EZ #
4040XP RWPA689	Standard	089817
4040XP EDA689	Extra Duty	089818
4040XP SCUSH689	Spring Cush	089820
4040XP H689	Hold Open	089822
4040XP HCUSH	Hold Open Cush	089821




4040XP

- 4040XP is LCN's most durable heavy duty closer designed for the most demanding, high use and abuse applications.
- Strongest pinion at 3/4" journal diameter, widest bearing at 5/8", stronger pinion teeth, V-shield™ seal with 20% longer life than conventional seals, 44% increased bearing load capacity.

- Cast Iron Forged Steel Arm
- Double Heat Treated Steel Pinion
- 4040XP can be used with all 4041 accessories.
- All stocked in Aluminum finish.

4040 Mounting Brackets



4040 16

- For doors where top jamb or parallel arm mounting cannot be used.




4040 18

- Required for hinge side mount where top rail is less than 3 3/4"



4040 18G

- Locates top jamb mounted closer flush with top of head frame face in flush ceiling condition. Plate requires 1 3/4" minimum head frame.



4040 18TJ

- Centers top jamb mounted closer vertically on head frame where face is less than 3 1/2". Plate requires 1 3/4" minimum head frame.

4040 18PA

- Required for parallel arm mounting where top rail is less than 5 1/2" measured from the top. Plate requires 2" minimum top rail.

Mfg #	Type	Finish	EZ #
4040 16 AL	Corner Bracket	Aluminum	035866
4040 18ALUM	Drop Plate	Aluminum	008559
4040 18G 695	Flush Drop Plate	Dark Bronze	035868
4040 18GALUM	Flush Drop Plate	Aluminum	008560
4040 18PAALUM	Parallel Arm Plate	Aluminum	008561
4040 18TJ 689	Top Jamb Plate	Aluminum	026791
4040 18TJ 695	Top Jamb Plate	Dark Bronze	072970

4040 Sentronic® Closer



4040SE

Mfg #	Voltage	EZ #
4040SE 120V 689	120VAC	073106
4040SE STD AL24V TBSRT	24VDC	072694

- Provides single point hold-open for fire and smoke barrier doors.
- Door is held open until current interruption releases the holding mechanism and the door closes.
- Single lever track arm closer is specifically designed for interior doors.
- Available 24VDC or 120VAC
- Non-sized for interior doors up to 4'0".
- Hold-open force is adjustable between 85° to 110° in approximately 3° increments (Push Side) and maximum to 95° (Pull Side).
- Momentary on/off switch board assembly for testing door release also provides over-voltage protection.
- Functions as a full rack and pinion closer when hold-open is not engaged or current is interrupted.
- Closer mounts on either push or pull side of the door.
- Interfaces with fire alarm systems.
- UL listed for smoke barrier or labeled fire doors. cUL listed for self-closing doors without hold-open. Tested and certified under ANSI Standard A156.15.
- Conforms to life safety code, NFPA 101.

