



FADINI
el abre verjas



Puertas & Portones Automaticos S.A. de C.V.
¡Nuestra pasión es la Solución!....

»BOLARDO PILONA HIDRALICO AUTOMATICO MARCA FADINI MOD.TALOS M50 Ø275MM X 20MM.

Item No.	<h1>TALOS M50</h1>																						
<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> <p>CERTIFIED</p> <ul style="list-style-type: none"> - ASTM F2656-15 C750 - PAS 68:2013 V/7500 (N3)/80 - IWA 14-1:2013 V/7200 [N3C]/80 <p>CRASH TEST: 7,5 t at 80 km/h</p> </div>																							
<p>Each item includes an automatic bollard complete with pit, cover plate, HRC steel moving cylinder, cataphoresis treated and polyester powder coated in RAL 7016 anthracite grey, head and rubber edge and 12 integrated amber-colour LED lights, approved retro-reflecting micro-prismatic high intensity adhesive film, electrolytic galvanized steel housing assembly with an oil-hydraulic actuator and motor-pump drive unit, two limit switch sensors (bollard in standing and lowered positions), release spanner with triangular socket.</p>																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Diameter</td><td>275 mm</td></tr> <tr><td>Height</td><td>1.000 mm</td></tr> <tr><td>Thickness</td><td>20 mm</td></tr> <tr><td>Post material</td><td>S355K2H steel</td></tr> <tr><td>Finishing of the post</td><td>RAL 7016 anthracite grey</td></tr> <tr><td>Pit</td><td>hot dip galvanization</td></tr> <tr><td>Impact resistance</td><td>700.000 J</td></tr> <tr><td>Breakout resistance</td><td>2.000.000 J</td></tr> <tr><td>Weight</td><td>770 kg</td></tr> <tr><td>Rising speed</td><td>20 cm/s (~ 5,0 s)</td></tr> <tr><td>Lowering speed</td><td>31 cm/s (~ 3,2 s)</td></tr> </table> <p><small>The pictures in this Price List are merely indicative.</small></p>		Diameter	275 mm	Height	1.000 mm	Thickness	20 mm	Post material	S355K2H steel	Finishing of the post	RAL 7016 anthracite grey	Pit	hot dip galvanization	Impact resistance	700.000 J	Breakout resistance	2.000.000 J	Weight	770 kg	Rising speed	20 cm/s (~ 5,0 s)	Lowering speed	31 cm/s (~ 3,2 s)
Diameter	275 mm																						
Height	1.000 mm																						
Thickness	20 mm																						
Post material	S355K2H steel																						
Finishing of the post	RAL 7016 anthracite grey																						
Pit	hot dip galvanization																						
Impact resistance	700.000 J																						
Breakout resistance	2.000.000 J																						
Weight	770 kg																						
Rising speed	20 cm/s (~ 5,0 s)																						
Lowering speed	31 cm/s (~ 3,2 s)																						
Drwg.No. 7671	<p>SECURITY OIL-HYDRAULIC AUTOMATIC BOLLARD TALOS M50</p>																						



CÓDIGO	SKU	MODELO	DESCRIPCIÓN
FD-00040-00	9690L	9690L	BOLARDO TALOS M50 275D 1000 ALT 20MM ESP



(229) 461-7028

portonesautomaticos@adsver.com.mx
portonesautomaticos@prodigy.net.mx



V06.23

(229) 927-5107, 167-8080, 167-8007, 151-7529



www.adsver.com.mx